



SPITWATER[®] 13-180H - HOT/COLD WATER CLEANER
INDUSTRIAL CLEANING & HEATING EQUIPMENT

SPECIFICATIONS

2700 P.S.I. (180 Bar) Pump Pressure
3750 P.S.I. Turbo Pressure (Optional)
13 Litres per minute Pump Volume
415 Volt 5.0 H.P. Electric Motor
2800 RPM Commercial Machine
Temperatures up to 90°

STANDARD EQUIPMENT

8 Metres High Pressure Hose
Insulated On/Off Pistol Assembly
Double Lance Assembly
High and Low Pressure Mode
Adjustable Chemical Injector with Bottle
Operators and Parts Manuals

<u>FEATURES</u>	<u>BENEFITS</u>
Interpump with Ceramic Pistons and Brass Head	<ul style="list-style-type: none"> Anodised crankcase and oversized bearings Longer pump life, non corrosive pump head
Water By-Pass Cooling Tank	<ul style="list-style-type: none"> Reduces potential damage to the pump in bypass
Inlet Water Filter	<ul style="list-style-type: none"> Stops debris from scoring pistons and seals
Pressure Gauge	<ul style="list-style-type: none"> Easily monitor pump performance
Powder Coated Zinc Annealed Chassis	<ul style="list-style-type: none"> Resistant to corrosion
Adjustable thermostat for hot water temperature control	<ul style="list-style-type: none"> Set the ideal temperature for any application