



www.oemgroup.com.au

Direct Fired Industrial Diesel Heater DC17

Technical Specifications		Included Features
Fuel Supply	Diesel / Kerosene	Steel Construction – Tank & Body
Heat Output	17 Kw	Portable with Carry Handle
Fuel Consumption	1.37 Kg/h	Robust & reliable
Airflow	357 m ³ /h	
Electricity Supply	Single Phase – 230 Volts	Inbuilt Safety Features: <ul style="list-style-type: none">➤ Temperature Limit Control➤ Electrical System Protection➤ Flame Out Sensor
Connected Load	140 W	
Minimum Room Vol.	153 m ³	
Running Time	11 Hours	
Fuel Tank Capacity	19 Litres	Run time fuel gauge
Manufactured in Korea to Australian Specifications & Standards		LED On/Off switch with Silicone cover



Call us: 9270 0200
For more info



Ad: [494-496 Great Eastern Highway, Redcliffe WA 6104](#)
Ph: (08) 9270 0200
E: contactoem@oemgroup.com.au

JETFIRE®



Model	DC17
Fuel Supply	Diesel/Kerosene
Heat Output	17kW
Fuel Consumption	1.37 kg/h
Air Flow	357m³/h
Electricity Supply	230V 1 phase 50 Hz
Connected Load	140W
Minimum Room Volume	145m³
Running Time (approx.)	11h
Fuel Tank Capacity	19L

Model	DC30
Fuel Supply	Diesel/Kerosene
Heat Output	30kW
Fuel Consumption	2.40 kg/h
Air Flow	765m³/h
Electricity Supply	230V 1 phase 50 Hz
Connected Load	190W
Minimum Room Volume	250m³
Running Time (approx.)	12.6h
Fuel Tank Capacity	38L



Model	DC50
Fuel Supply	Diesel/Kerosene
Heat Output	50kW
Fuel Consumption	4.12 kg/h
Air Flow	1036m³/h
Electricity Supply	230V 1 phase 50 Hz
Connected Load	280W
Minimum Room Volume	420m³
Running Time (approx.)	9.4h
Fuel Tank Capacity	49L

Model	DI16
Fuel Supply	Diesel/Kerosene
Heat Output	16.5kW
Fuel Consumption	1.37 kg/h
Electricity Supply	230V 1 phase 50 Hz
Connected Load	70W
Minimum Room Volume	145m³
Running Time (approx.)	6h
Fuel Tank Capacity	13L



Ad: [494-496 Great Eastern Highway, Redcliffe WA 6104](#)
 Ph: (08) 9270 0200
 E: contactoem@oemgroup.com.au