

HP12-110E GT

Cold Water Cleaner



Picture showing wall mount option

Specifications

- ⇒ 1650 P.S.I. (110 Bar) pump pressure
- ⇒ 2400 P.S.I. turbo pressure (optional)
- ⇒ 12 Litres Per Minute pump volume
- ⇒ 240 Volt 3 H.P. electric motor
- ⇒ 1450 RPM low speed pump
- ⇒ 15 amp plug Single phase
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Single lance assembly
- ⇒ High & Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ Operators and parts manuals

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduced maintenance costs
Water cooling tank	Reduces potential damage to the pump in bypass
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
Galvanised base with stainless steel cover	Corrosion resistant – Ideal for wet areas Wall & floor mounted options available
Bypass shutdown timer	Increases life of the machine by shutting down when not in use

For more information,
please visit our website

spitwater.com.au