



PRESSURE CLEANERS



Made in Australia SINCE 1982

HP23-350DE

Cold Water Cleaner



Specifications

- ⇒ 5000 P.S.I. (350 Bar) pump pressure
- ⇒ 6200 P.S.I. turbo pressure (optional)
- ⇒ 23 Litres Per Minute pump volume
- ⇒ 23 H.P. Kubota water cooled diesel motor
- ⇒ 1450 RPM low speed pump
- ⇒ Electric start
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High and Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ Operators and parts manuals

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduce maintenance costs
Water cooling tank and low level cut off	Reduces potential damage to the pump in bypass
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge and hour metre	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis	Resistant to corrosion and greater manoeuvrability over tough terrain

Battery Isolator

Keeps battery in good condition and protects the operator in an emergency

For more information, please visit our website

spitwater.com.au

TOUGH + READY
CREATED BY OTTICO