



PRESSURE CLEANERS



Made in Australia SINCE 1982

# SW15-200DES

Hot/Cold Water Cleaner



### Specifications

- ⇒ 3000 P.S.I. (200 Bar) pump pressure
- ⇒ 4200 P.S.I. turbo pressure (optional)
- ⇒ 15 Litres Per Minute pump volume
- ⇒ 13 H.P. Hatz Silent diesel motor
- ⇒ 1800 RPM
- ⇒ 12 Volt Burner system
- ⇒ Temperature up to 90°
- ⇒ Heavy duty machine

### Standard Equipment

- ⇒ 10 Metres high pressure hose
- ⇒ Insulated on/off pistol assembly
- ⇒ Double lance assembly
- ⇒ High and Low pressure mode
- ⇒ Adjustable chemical injector with bottle
- ⇒ Operators and parts manuals

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduce maintenance costs
Water cooling tank	Reduces potential damage to the pump in bypass
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis	Resistant to corrosion and greater manoeuvrability over tough terrain
Adjustable thermostat for hot water temperature control	Set the ideal temperature for any application
Battery Isolator and emergency stop	Keeps the battery in good condition and protects the operator in an emergency

For more information, please visit our website

[spitwater.com.au](http://spitwater.com.au)

**TOUGH + READY**  
CREATED BY OTTICO