

PRESSURE CLEANERS



HP12150DE 2250PSI 12L/min

TECHNICAL SPECIFICATIONS

POWER TYPE		Diesel
TEMPERATURE		Cold Water
PUMP PRESSURE	PSI	2250
	BAR	150
FLOW RATE	L/min	12
MOTOR		Kubota OC60
	HP	6.5
FUEL CAPACITY	L	3.6
DIMENSIONS L x W x H	mm	823x605x761
WEIGHT	kg	110
INTERPUMP PUMP		W140
PUMP SPEED	RPM	1450
DRIVE		Oz-Tuff Belt Reduction
WHEELS		Never-flat Polyurethane

Not suitable for domestic use. Actual products may differ slightly in apperance to images shown. OEM Group reserves the right to modify design features and technical data without notice.





STANDARD HIRE EQUIPMENT

- Heavy Duty Gun & Back Part Lance (#PA30209230)
- ✓ Commercial Dual Front Part Lance (#PA41092200)
- ✓ 10M R2 High Pressure Hose (#46609)
- Standard 15° 035 Nozzle(#70014/3515)

FEATURES

- ✓ Fully Serviceable
- ✓ Genuine Italian-made Interpump Pump
- Non-corrosive Brass Head Pump with Stainless Steel Valves and Ceramic Pistons
- ✓ 100% Bypass into Cooling Tank
- ✓ Pressure Gauge
- ✓ Low speed 1450RPM Pump
- Powder Coated Zinc Annealed Chassis with Roll Frame and Reel Mount

YOUR PARTNER IN

PRODUCTIVITY

- ✓ Never-flat Polyurethane Wheels
- Electric Key Start
- ✓ Washable Inlet Water Filter
- Adjustable Chemical Injector

GROUP

🖌 Australian Made

- **\$** +61 8 9270 0200
- contactoem@oemgroup.com.au