

TECHNICAL SPECIFICATIONS

POWER TYPE		Diesel
TEMPERATURE		Hot Water
PUMP PRESSURE	PSI	3000
	BAR	200
FLOW RATE	L/min	15
MOTOR		Hatz 1D81C
	HP	8
FUEL CAPACITY	L	35
DIMENSIONS L x W x H	mm	1110x1110x1005
WEIGHT	kg	424
INTERPUMP PUMP		E3C2515
PUMP SPEED	RPM	1450
DRIVE		Direct Drive

STANDARD HIRE EQUIPMENT

- ✓ Commercial Gun with Back Part Lance (#PA30209230)
- ✓ Commercial Dual Front Part Lance (#PA41092200)
- ✓ 30 Metre High Pressure Hose (#46602/30)
- ✓ Free Standing Hose Reel (#SWA129/KIT)
- ✓ Standard 15° 045 Nozzle (#70014/4515)

FEATURES

- ✓ Fully Serviceable
- ✓ Genuine Italian-made Interpump Pump
- Non-corrosive Brass Head Pump with Stainless Steel Valves and Ceramic Pistons
- 100% Bypass into Cooling Tank
- ✓ Pressure Gauge
- ✓ Powder Coated Zinc Annealed Frame
- ✓ Washable Inlet Water Filter
- ✓ Electric Key Start
- ✓ Emergency Stop
- Lockable Battery Isolator
- ✓ Hour Metre
- ✓ Skid Mounted
- ✓ Forklift Pockets
- ✓ Low Level Water Cut Off
- ✓ 12V Burner System
- ✓ 3/8" Seamless Heating Coil Mild Steel
- ✓ Adjustable Temperature up to 90°C
- Adjustable Chemical Injector
- 🖌 Australian Made

Not suitable for domestic use. Actual products may differ slightly in apperance to images shown. OEM Group reserves the right to modify design features and technical data without notice.



- 🐱 contactoem@oemgroup.com.au
- www.oemgroup.com.au

